

**Series 4, island cooker hood, 120 cm,  
Stainless Steel  
DIB128G50I**



**With its stainless steel finish, this high performer complements any island hob in form and function.**

- **Extraction rate:** Optimal performance to keep your kitchen odour free in no time
- **LED-Illumination:** The energy-saving lighting provides white and good lighting for the hob area.
- For fast and effective extraction, the intensive speed setting removes strong kitchen odours quickly and effectively.
- **Intensive speed setting with reset:** automatically resets the hood to normal speed setting
- Ducted or Non-ducted Options

---

**Technical Data**

Typology : Island/Ceiling

Approval certificates : not relevant

Height of product, without chimney : 340 mm

Net weight : 29.4 kg

Type of control : Electronic

Boost position output recirculating : 575.0 m<sup>3</sup>/h

Maximum output recirculating air : 545 m<sup>3</sup>/h

Boost position air extraction : 705 m<sup>3</sup>/h

Number of lights : 4

Diameter of air outlet : 120 / 150 mm

Grease filter material : Washable stainless steel

Odour filter : No

Operating Mode : Convertible

Delay Shut off modes : 30 min

Optional accessories : DHZ5477

Type of lamps used : LED

Total power of the lamps : 4 W

Voltage : 230 V

Frequency : 50 Hz

Installation typology : Island

Material body : Stainless steel

Approval certificates : not relevant

Dimensions of the product, with chimney (if exists) (in) : / x x

Dimensions of the packed product : 18.50 x 29.92 x 51.37

Net weight : 65.000 lbs

Gross weight : 94.000 lbs

Motor location : Integrated motor in hood chimney

No-return airflow flap : No

Dimensions of the product, with chimney (if exists) : x 1175.0 x 610.0 mm

Dimensions of the packed product (HxWxD) : 470 x 760 x 1305 mm

Net weight : 29.4 kg

Gross weight : 42.6 kg



## **Series 4, island cooker hood, 120 cm, Stainless Steel DIB128G50I**

**With its stainless steel finish, this high performer complements any island hob in form and function.**

---

### **Design**

- Box design for Ceiling mounting
- Brushed stainless steel and glass panel
- Electronic touch control on Black full width glass panel, on one side
- Chromed logo strip on the chimney
- Sleek White LED indication of settings

### **Key Functions**

- Maximum extraction rate according to EN 61591: 705 m<sup>3</sup>/h
- Maximum blower performance: 745 m<sup>3</sup>/h (freeblowing)
- 4 fan speed settings (three plus intense)

### **Comfort**

- 4 x 4 W LED lighting
- Intensive speed automatically switches back to previous setting after 10 minutes
- 4 metal grease filters, high grade stainless steel Baffle filters
- Noise level from 55 dB to 77 dB

### **Technical information**

- For Ceiling mounting only
- Suitable for ducted or recirculating operation
- Dimensions of the product, with chimney (if exists)  
(HxWxD mm): 1000 x 1175 x 610
- Minimum clearance to gas/electric cook top: 750 mm
- Length electrical supply cord: 150 cm
- Ducting connection: 150mm/120mm diameter

*\* In accordance with the EU-Regulation No 65/2014*

## Series 4, island cooker hood, 120 cm, Stainless Steel DIB128G50I

